



Integrity Quality Service

**Manufacturer and Exporter of Concrete
Construction Machinery & Accessories**

Catalogue 2012



Honway Machinery

China Honway Technology Co., Ltd

ADD: Building 5 Changhua Park, Yuelu District, Changsha, China 413100

Tel : +86 731 84223603 Fax : +86 731 84227598

Mail : sales@honwaymachinery.com

Web: www.honwaymachinery.com

ABOUT HONWAY



Honway Technology company Co.,Ltd (Chinese based) have established its reputation as a leading manufacturer in the following market:

Concrete milling – scarifying and planning concrete, to remove coatings, dirt, oil, etc on the floor. (Also suitable to asphalt).



Concrete Waterproof-grooving, roughening concrete, for cohere the old layer with the new one.

Performance Flooring - commercial or non commercial floor, industry floor, epoxy resin coatings & floor preparation.

Concrete saws and screeds - civil construction, road repair, small area work.

We are not only oriented to be a supplier of processing concrete equipments, but also a sound adviser and server for clients that work in the construction project. Our area of activity encompasses concrete structure: industrial floor, tunnel, road repair, above and below ground parking deck/basements, bridges, floor preparation, etc.

For additional information or technical assistance, kindly contact us!



ADD: Room 1508 Building 5 Changhua Park. Yuelu District, Changsha, China

ZIP: 410000

Sales Department

Tel: 0086-0731-84223603

Fax: 0086-0731-84227598

Cell Phone: 0086-13077380137

Email: sales@honwaymachinery.com

Service Department

Tel: 0086-0731-84223603

Fax: 0086-0731-84227598

Cell Phone: 0086-13319592705

Email: services@honwaymachinery.com

Branch Office

Add: Room 0513, Yongtai Building Congyun Rd, Baiyun District, Guangzhou, China

ZIP: 510000

Tel: 0086-020-36335937

Fax: 0086-020-36335937

Cell Phone: 0086-18973736109

Email: branch@honwaymachinery.com



SERVICE

Pre-sales Service

- 1, Customers browse website and catalogue and inquire the sales the product by telephone, email or talking tools;
- 2, Specifications, construction conditions, and technical details should be communicated, so the sales could choose out the appropriate products for customers, and customers know if the products are suitable for them or not;
- 3, Sales present the list of spare parts, and make a suggestion.

In-sale Service

- 1, Customer sign the contract with sales, or come to company to inspect, negotiate, and sign the contract;
- 2, The service department place the order, supervise manufacturing, book ship, help clients clear customs;
- 3, We inspect every steps of order, and report the problems and process of manufacture and transportation to clients.

After-sale Service

- 1, Any problem occur, the after-service department provides a solution within one hour;
- 2, We promise a timely supply of any ordered accessories;
- 3, During 180days of warranty, spare parts are free of charge;
- 4, Technical support&service lasts whole life.

Service Online

Tel: 0086-0731-84223603

Fax: 0086-0731-84227598

Cell Phone: 0086-13319592705

Email: services@honwaymachinery.com

CONTENT

Concrete Grinder(HWG400).....	1
Concrete Grinder(HWG45/60/78).....	3
Concrete Grinder(HWG59/70).....	4
Concrete Grinder(HWG90).....	5
Diamond Tools.....	6



Grinding and Polishing Machinery

Grinding and polishing machine can be used for coarse grinding, medium grinding, fine polishing, crystallizing, preparation, maintenance. It is not only applied for concrete, but also for millstone, marble, granite, and terrazzo.



Performance

Aluminum alloy gearbox guarantee quality;

Big motor: good for large area; inverter: grinding and polishing;

Two motors to choose: 380-400V, Three P; 220-240V, One P;

Water tank and vacuum port provide wet and dry grinded and polished;

Vacuum outlet and rubber skirt prevent dust from entering the machine.



Ideal for

Smoothing rough surfaces or trowel marks;

Grinding concrete or terrazzo;

Repairing damaged concrete slabs;

Removing epoxy thin-coats;

Grinding sharp grout, mastic, flint and granite;

Leveling and smoothing uneven surfaces.



Concrete Grinder(HWG400)

Performance

The height of handlebar can be adjusted;

Vacuum outlet and rubber skirt prevent dust from entering the machine;

Circuit breaker protects the machine from motor overload;

Mounting discs are connected by rubber pads, to avoid the slight vibration which is caused by wear of gear wheel;

Foldable hand makes transportation and storage easy and compact.

Smoothing rough surfaces or trowel marks;

Repairing damaged concrete slabs;

Removing epoxy thin-coats;

Grinding sharp grout, mastic, flint and granite;

Leveling and smoothing uneven surfaces;

Power	4KW	Voltage	380V 3Phase
Current	16A	Rated revolution	1400rpm
Disc Diameter	400mm	N.W	125KG
Water/Vacuum port	Yes	G.W	135KG



Disc plate of HWG-400.



Disc plate equips 8 or 16 pieces of diamond tools.



Vacuum port and the skirt prevent dust from outside.



Handle, can be adjusted to different degree.



Machine can be folded.



Handle bar adjust height of handle.



Skirt stick to machine by nylon.



Grinded floor compared to ungrinded.



Grinded floor.



Honway Machinery



Parameter

Model	HWG 45	HWG 60	HWG 78
Weight	135KG	190KG	240KG
Work Area	450mm	600mm	780mm
Motor	5.5HP Siemens	7.5HP (5.5KW) Siemens	10HP (7.5KW) Siemens
Inverter	7.5HP	10HP	15HP (7.5KW)
Voltage	220/380/460V	220/380/460V	220/380/460V
Hertz	50/60HZ	50/60HZ	50/60HZ
Current	12A	14A	16A
Disc Diameter	200mm*3	230mm*3	250mm*3
Main Plate speed	50-350rpm	50-350rpm	50-400rpm
Small Plates speed	300-1750rpm	300-1750rpm	300-1750rpm
Disc Drive	Gear drive type	Gear drive type	Gear drive type
Extra weight	30KG	30KG	30KG
Water Tank	30L	30L	30L
Noise	65DB	65DB	65DB
Packing	0.8 cube	0.8 cube	1.2 cube



Controlling Panel



Power Plug



Distance toward Wall only 5mm.




Working Site



Working Site



Planetary Cover



Parameter

Model	HWG 59	HWG 70
Weight	200KG	280KG
Work Area	590mm	700mm
Motor	10HP (7.5KW) Siemens	15HP (11KW) Siemens
Inverter	10HP/15HP	18.5HP (15KW)
Voltage	220/380/460V	380/460V
Hertz	50/60HZ	50/60HZ
Current	16A	24A
Disc Speed	300-1750rpm	300-2000rpm
Disc Diameter	320mm*4	380mm*4
Disc Drive	Gear drive type	Gear drive type
Extra weight	45KG	45KG
Water Tank	30L	30L
Noise	65DB	65DB
Packing	0.8 cube	1.15 cube




Water Switch



Inverter Box



Handle can be turned around 360 degree



Working Site



Working Site



Wheel Trace

4 Planetary Concrete Grinder(HWG 90)



Parameter

Weight	300KG	Work Area	900mm
Motor	15HP Siemens	Inverter	18.5HP
Voltage	380/460V	Hertz	50/60HZ
Current	24A	Disc Diameter	300mm*4
Main Plate speed	50-400rpm	Small Plates speed	300-2000rpm
Disc Drive	Gear drive type	Extra weight	45KG
Water Tank	30L	Noise	65DB

Diamond Tools



Picture	Item	Application	Description
	DT0001	Diamond tools	Metal 40mmx12mmx12mm #20 #30 #60 #80 #150 #300
	DT0002	Dry Honey Type Polishing Pad	Resin Dia:80mm(3") Thick: 1.5mm #50 #100 #200 #400 #800 #1500 #3000 buff
	DT0003	Dry Concrete Polishing Tools	Resin or Metal Dia:80mm(3") Thick: 6mm #50 #100 #200 #400 #800 #1500 #3000 buff
	DT0004	Dry Concrete Polishing Tools	Resin or Metal Dia:80mm(3") Thick: 10mm #50 #100 #200 #400 #800 #1500 #3000 buff
	DT0005	Dry Concrete Polishing Tools	Dia:89mm(3,5") Thick: 8mm #50 #100 #200 #400 #800 #1500 #3000 buff
	DT0006	Dry Concrete Polishing Tools	Dia:80mm(3") Thick: 10mm #50 #100 #200 #400 #800 #1500 #3000 buff
	DT0007	Dry Concrete Polishing Tools	Dia:80mm(3") Thick: 10mm #50 #100 #200 #400 #800 #1500 #3000 buff
	DT0008	Dry Concrete Polishing Tools	Resin or Metal Dia:80mm(3") Thick: 10mm #50 #100 #200 #400 #800 #1500 #3000 buff